Serial No.: 10/629,475 Filed: July 29, 2003 Page: 2 of 13

## Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

## **Listing of Claims**:

Claims 1-39 (Canceled)

40. (Withdrawn) A method for verifying data integrity communicated between an operator interface and a remote control device, the operator interface and remote control device having associated device numbers, said method comprising:

communicating a signal on a channel between the operator interface and the remote control device, the signal including a device number, channel number, and checksum;

receiving the signal including the device number, channel number, and checksum; verifying the checksum to confirm integrity of the signal;

determining if the channel and the channel number match; and

determining if the transmitted device number corresponds to the device number of the remote control device.

- 41. (Withdrawn) The method according to claim 40, further comprising: determining that data integrity is invalid; and utilizing, by the remote control device, a last set of valid data.
- 42. (Withdrawn) The method according to claim 40, further comprising: determining that data integrity is invalid; and disabling the remote control device.

Serial No.: 10/629,475 Filed : July 29, 2003 Page : 3 of 13

(Withdrawn) The method according to claim 40, wherein the remote control device is a 43. robot.

- (Withdrawn) The method according to claim 40, wherein the determining of the channel 44. occurs during a robot competition.
- 45. (Withdrawn) The method according to claim 40, wherein each of the device number, channel number, and checksum are transmitted in a single data packet.

Serial No.: 10/629,475 Filed: July 29, 2003 Page: 4 of 13

46. (Withdrawn) A system for determining a channel of communication between an operator interface and a remote control device, the operator interface and remote control device having associated device numbers, said method comprising:

means for assigning the channel to the operator interface;

means for transmitting a signal on a first channel, the signal including a device number, channel number, and checksum;

means for selecting, by the remote control device, a second channel to receive the signal; means for receiving the signal including the device number, channel number, and checksum;

means for verifying the checksum to confirm integrity of the signal;
means for determining if the second channel and the channel number match; and
means for determining if the transmitted device number corresponds to the device
number of the remote control device.

- 47. (Withdrawn) The system according to claim 46, further comprising locking the channel of the remote control device.
- 48. (Withdrawn) The system according to claim 46, wherein the remote control device is a robot.
- 49. (Withdrawn) The system according to claim 46, wherein the determining of the channel occurs during a robot competition.
- 50. (Withdrawn) The system according to claim 46, wherein each of the device number, channel number, and checksum are transmitted in a single data packet.
- 51. (Withdrawn) The system according to claim 46, further comprising selecting a different channel if the second channel and channel number do not match.

Serial No.: 10/629,475 Filed: July 29, 2003 Page: 5 of 13

52. (Withdrawn) A system for verifying data integrity communicated between an operator interface and a remote control device, the operator interface and remote control device having associated device numbers, said method comprising:

means for communicating a signal on a channel between the operator interface and the remote control device, the signal including a device number, channel number, and checksum;

means for receiving the signal including the device number, channel number, and checksum;

means for verifying the checksum to confirm integrity of the signal;
means for determining if the channel and the channel number match; and
means for determining if the transmitted device number corresponds to the device
number of the remote control device.

- 53. (Withdrawn) The system according to claim 52, further comprising: means for determining that data integrity is invalid; and means for utilizing, by the remote control device, a last set of valid data.
- 54. (Withdrawn) The method according to claim 52, further comprising: determining that data integrity is invalid; and disabling the remote control device.
- 55. (Withdrawn) The system according to claim 52, wherein the remote control device is a robot.
- 56. (Withdrawn) The system according to claim 52, wherein the determining of the channel occurs during a robot competition.
- 57. (Withdrawn) The system according to claim 52, wherein each of the device number, channel number, and checksum are transmitted in a single data packet.

Applicant: David A. Norman, et. al. Serial No.: 10/629,475 Filed: July 29, 2003 Page: 6 of 13

Claims 58-76 (Canceled)

Serial No.: 10/629,475 Filed : July 29, 2003 : 7 of 13

Page

77. (Previously Presented) A method for providing safety at a robot competition, said method comprising:

commencing the robot competition; and

providing a remote disabling mechanism for the robot competition, the remote disabling mechanism operable to selectively disable a plurality of robots independent of persons operating the plurality of robots.

- 78. (Currently Amended) The method according to claim 77, wherein the selective disable selectively disabling the plurality of robots includes disengaging power to the plurality of robots.
- 79. (Currently Amended) The method according to claim 77, wherein the selective disable selectively disabling the plurality of robots includes disabling control signals on the plurality of robots.
- 80. (Currently Amended) The method according to claim 77, wherein the remote disabling mechanism is includes an emergency stop button, the emergency stop button being readily accessible and operable to disable all robots in a local vicinity of the emergency stop button.
- 81. (Original) The method according to claim 80, wherein the local vicinity is within approximately 500 feet of the emergency stop button.

Serial No.: 10/629,475 Filed: July 29, 2003 Page: 8 of 13

82. (Currently Amended) A system for providing safety at a robot competition, said system comprising:

<u>a remote disabling mechanism operable to means for selectively disabling disable</u> a plurality of robots independent of persons operating the plurality of robots; and

means, coupled to each robot, for disabling the robot in response to the means for selectively disabling remote disabling mechanism.

- 83. (Currently Amended) The system according to claim 82, wherein the means for disabling remote disabling mechanism is <u>further</u> operable to disengage power to the plurality of robots.
- 84. (Currently Amended) The system according to claim 82, wherein the means for disabling remote disabling mechanism is <u>further</u> operable to disable control signals on the plurality of robots.
- 85. (Currently Amended) The system according to claim 82, wherein the <u>remote disabling</u> mechanism includes an emergency stop button, and wherein the emergency stop button is <u>operable to disable disabling occurs for</u> all robots in a local vicinity of the emergency stop button.
- 86. (Original) The system according to claim 85, wherein the local vicinity is within approximately 500 feet of the emergency stop button.

Serial No.: 10/629,475 Filed : July 29, 2003 : 9 of 13 Page

87. (Currently Amended) A system for providing safety at a robot competition, said system

comprising:

a first device operable to selectively disable at least one robot independent of a person

operating the at least one robot, wherein the first device is located remotely from the at least one

robot;

at least one first radio in communication with said first device;

a second radio, coupled to a first robot and in communication with the at least one of the

first radio radios, the second radio operable to receive a signal for disabling the first robot from

at least one of the first radios; and

a second device operable to disable the first robot in response to the a received signal for

disabling the first robot, wherein the second device is coupled to the first robot.

88. (Currently Amended) The system according to claim 87, wherein the selective disable the

first device operable to selectively disable the robot includes the first device being operable to

disengage disengaging power to the at least one robot.

89. (Currently Amended) The system according to claim 87, wherein the selective disable the

first device operable to selectively disable the robot includes the first device being operable to

diable disabling control signals on the at least one robot.

90. (Currently Amended) The system according to claim 87, wherein the remote disabling

mechanism is the first device includes an emergency stop button being readily accessible and

operable to disable all robots in a local vicinity of the emergency stop button.

91. (Original) The system according to claim 90, wherein the local vicinity is within

approximately 500 feet.